

"THE TANK" FIXED BASKET BLASTER

Our fixed basket line removes rust, dust, dirt, and other contaminants, without part on part tumbling. Most versatile blaster on the market.





Offering versatile door options. Whether you prefer an automatic lift-up or a manual swing door.



0

Easy basket jigging setup for any shape parts with adjustable spring loaded rods.





Optional voltage available ranging from 230v - 575v.



710 E. 17th St. • Wichita, Kansas 67214 TG: 800-835-0218 • 316-265-7997 Fax: 316-265-0013 sales@Isindustries.com www.lsindustries.com





SPECIFICATIONS: Pre-Engineered Models

MODEL#	DIMENSIONS (L X W X H)	BASKET DIMENSIONS (L X DIA)	BASKET CAPACITY	WHEEL POWER
LSBH - 2	66" x 36.5" x 75"	32" x 23"	500 lbs	1 - 10 hp
LSBH - 4	74" x 44" x 72"	46" x 25.5"	500 lbs	2 - 7.5 hp
LSBH - 8	75" x 51" x 78.5"	60" x 30"	1,000 lbs	2 - 10 hp
LSBH - 12	192" x 84" x 108"	168" x 50"	1,500 lbs	6 - 15 hp
LSBH - 76 x 35	101" x 58" x 145"	76" x 35"	1,000 lbs	2 - 10 hp
LSBH - 108 x 36	144" x 72" x 132"	108" x 36"	1,500 lbs	4 - 10 hp
LSBH - 168 x 80	240" x 10'6" x 132"	168" x 80"	1,500 lbs	6 - 15 hp



Before

FEATURES:

- Door available as manual swing or automatic lift up for overhead loading
- LS Turboshot[™] blast wheel design
- Door safety switch
- One button push operation with adjustable cycle times
- Easily replaceable cabinet/liners
- Easy basket jigging setup for any shape parts - spring loaded rods
- Automatic reversing cycle for thorough cleaning
- Full load of steel shot abrasive media included; customer choice of S70 - S330
- Shot load ampimeter to maintain proper shot load

OPTIONS:

- Motor upgrades for faster performance
- Heavier duty construction
- · Removable basket
- Additional baskets
- Special designed fixturing
- Automated kick out basket with table
- Dust collection, sized to fit
- Removable stand control panel
- Factory assist install & training
- Optional voltage available in:
 - 230v/3ph/50hz
 - 380v/3ph/50 hz
 - 440v/3ph/60hz
 - 575v/3ph/60 hz



After

^{***}More sizes available***