



## **SPECIFICATIONS:**

RANGES	MINIMUM	MAXIMUM
OPENING SIZES HEIGHT	12"	72"
OPENING SIZES WIDTH	12"	72"
NO. OF WHEELS FOR COVERAGE	4	24
HORSEPOWER	10	75
WEIGHT CAPACITY (LINER FOOT)	300	1,500
LINE SPEED	3'	30'

\*\*\*More options available\*\*\*

## **FEATURES:**

- All steel welded construction
- Analog amperage meter for shot load control
- UL and CSA registered
- Electrical components
- 220V/3PH/60HZ or 440V/3PH/60HZ
- Cycle timer to control the duration of the blasting cycle

## **IDEAL FOR:**

- Die castings
- Automotive wheels
- Ferrous and non-ferrous castings
- Weldaments
- Forged parts
- Fabrications
- Many sizes and a variety of shapes
- Concrete etching
- Heat-treated parts
- Better coverage and thorough cleaning
- Superior dust collection
- No pit designs

## **POPULAR OPTIONS:**

Maintenance/

Service Platform

Extension

**Conveyor Transfer** 



Off

Parts Blow





Magnetic Valves



Collection



Service Package



Variable **Frequency Drives** 



Ductwork

710 E. 17th St. · Wichita, Kansas 67214 · TG: 800-835-0218 · 316-265-7997 · Fax: 316-265-0013 sales@lsindustries.com · www.lsindustries.com