


LS Industries Blast Rooms are designed to deliver the best surface preparation you can achieve, while producing a safe environment and meet production rates.

**CUSTOMED  
ENGINEERED  
SOLUTIONS!**




The suction fan creates a negative pressure at one end of the blast room.



1 - 4 Operators are common while in use; depending on the size. But can design for as many as needed.



Bucket elevator reclaim system.



Floor choices: Corner shut or shoveling, complete single floor, with simple screw, "U" shaped, "H" shaped, "L" shaped, or full double floor.



710 E. 17th St. • Wichita, Kansas 67214  
TG: 800-835-0218 • 316-265-7997  
Fax: 316-265-0013  
sales@lsindustries.com  
www.lsindustries.com

# SPECIFICATIONS:

CATEGORY	RANGES
Typical widths	10' - 80'
Typical heights	10' - 30'
Typical lengths	10' - 250'
Operators	1 - 12 (1 - 4 is common)

\*\*\*More options available\*\*\*

## FEATURES:

- Storage hopper for abrasive media
- Protection equipment for one operator with grade "D" breathing air
- Abrasive blast room structure and dust collector
- Multiple abrasive recovery and cleaning system styles available
- 6 ft<sup>3</sup> shot blasting pressure pot with larger sizes available
- Operator protection equipment
- Main electrical panel
- NEMA-12 control panel
- Swing-type of bifold and roled up work doors
- LED lighting

## COMPONENTS:



Enclosure



Media Reclaim System



Cartridge Dust Collector



Blast Machine



Protection Equipment



Ductwork

## OPTIONS:



HMI / PLC Touchscreen



Robotics



Service Package

- Fire suppression
- Roll-up doors
- Crane opening at top
- Pass through doors
- Axis man lifts
- Heavy duty steel panels
- Rail car
- Tracks and turntables
- HEPA filter