

The 17B Tumble Blaster removes rust, dust, dirt, and other contaminants with a full 360 degree blast.



CATEGORY

DETAILS

Basket (ft³)	17
Overall Dimensions (l x d x h)	71" x 50" x 85"
Number of Blast Wheels	1 - 15HP
Basket Size (l x dia.)	33" x 36"
Dust Collector	DC-2



Before



After

FEATURES:

- Heavy-duty steel construction
- 0.25" manganese liners in all direct shot patterns
- Shot wheel is lined with replaceable wear resistant plates
- Double-walled bearing protection with seal
- Full load of abrasive media (S-110 to S-330)
- Large air intake for cooler operation and efficient dust collection
- NEMA-12 enclosure (all electrical components are UL & CSA)
- Door safety switch to shut down machine when in use
- Basket drive motor
- Standard cycle timer
- Standard ammeter for shot load indication

OPTIONS:

- Fixture basket
- Removable basket
- Small parts basket
- Manganese cabinet for long life
- Dust collector upgrade
- Motor upgrades
- Heavy basket screens
- Voltages
 - 230V/3PH/50HZ
 - 380V/3PH/50HZ
 - 440V/3PH/60HZ
 - 575V/3PH/60HZ



Wire mesh baskets can hold multiple and a variety of parts in one blast. The part on part contact helps with the cleaning process.



Constructed with heavy-duty steel construction. The door and cabinet are lined with replaceable wear resistant plates for long time use.



The LS TurboShot™ blast wheel uses high volume, bi-directional, medium velocity to efficiently and effectively disperse shot media for a 360 degree blast.

710 E. 17th St. • Wichita, Kansas 67214
 TG: 800-835-0218 • 316-265-7997
 Fax: 316-265-0013
sales@lsindustries.com
www.lsindustries.com