

Our 8-FTW was designed to remove oil, grime, dirt, and other contaminants off any part that can fit through the entrance.



FEATURES:

- 7 - day advance heat up timer for early start-up
- Filter debris screen
- Easy controls (On / Off)
- Digital amp meters
- Heavy-duty galvanized belt material
- Insulated wash tank
- Fixed speed conveyor belt
- Conveyor sprockets on entrance
- Conveyor drive sprockets at the exit for belt support and drive



Angled sprayers to get a 360° clean on your parts.



Power exhaust to remove varying volumes of steam.

OPTIONS:

- 1.5HP Power Exhaust
- Liquid level control system
- Oil skimmer
- Digital thermostat
- Stainless steel
- Pump sound insulation package
- Hot air blow-off
- Motor powered steam exhaust
- HMI/PLC touchscreen
- Automatic sludge drag-out conveyor
- Small parts basket



Easy to use controls for minimum training and early start-up.

CATEGORY

DETAILS

Wash tank capacity	180 Gallons
Electrical	460V/3PH/60HZ
Tunnel opening (w x h)	18" x 16"
Machine Length	8"
Wash section with vestibules	4'
Electrical Heat	30kW
Seal-less pump	180 GPM
Conveyor belt	24" w
Conveyor belt drive	0.5HP

WATCH ME IN ACTION!



SCAN HERE

710 E. 17th St. • Wichita, Kansas 67214
 TG: 800-835-0218 • 316-265-7997
 Fax: 316-265-0013
sales@lsindustries.com
www.lsindustries.com