

LS Industries ULS1980 uses high frequency sound waves for efficiency and versatility to achieve a gentle, safe, and environmentally friendly cleaning of metal, glass, rubber, ceramic, and more.



## FEATURES:

- Oil separation with LS fluid dynamics
- Automatic nightly eco mode
- Synchronized 28 khz generators
- Replaceable 1 kw transducer sets
- Floating/peek water sensor level
- Insulated top lid

## OPTIONS:

- 20" size stainless steel reusable filtering device
- Automatic water refilling system
- Hybrid heating system
- Closed basket for small parts
- Ethernet delta module
- Automatic top lid open/close
- Perimeter stream extraction system
- Highest cleaning performance chemicals
- Oscillation platform lift that boosts cleaning by 50% on more complex parts

## ADVANTAGES:

- Most efficient cleaning in heavy-duty applications
- Cleans openings less than 0.04"
- Modular design
- No damage to parts
- Maintains a clean work environment
- Non-abrasive method
- Easy to use and low maintenance
- Less detergent consumption
- Savings on labor cost
- Robust heavy-duty design
- 80% of time savings



LS Ultrasonic Washers are insulated with a perimeter sealed top lid, 2" thermal & acoustic insulation. It also has an automatic nightly economy mode.



The Oil Skimmer separates the oil to provide low maintenance.



The control panel with a multi language touch screen.

### CATEGORY

### DETAILS

|                         |                              |
|-------------------------|------------------------------|
| Tank Dimensions         | 125.9" l x 80.7" d x 45.3" h |
| Tank Capacity           | 1,980 Gallons                |
| Loading Tray Dimensions | N/A                          |
| Ultrasonic Power        | 25 kW                        |
| Heating Power           | 44 kW                        |
| Maximum Lift Load       | N/A                          |
| Automatic Top Lid       | Included                     |



710 E. 17th St. • Wichita, Kansas 67214  
 TG: 800-835-0218 • 316-265-7997  
 Fax: 316-265-0013  
[sales@lsindustries.com](mailto:sales@lsindustries.com)  
[www.lsindustries.com](http://www.lsindustries.com)