

LS Industries LSE-30 is designed to clean the exterior surfaces of various sizes of cylinders. Approximately 15 cylinders per hour.



FEATURES:

- Dual 10HP impeller motors standard
- Manganese alloy cylinder roller shafts
- Manual hinged door with integrated door safety switch
- Nema 12 electrical enclosure
- Digital amp meters
- All components UL and/or CSA registered
- Full load of steel shot abrasive media included
- Air operated cylinder lift
- EPDM rubber door seal to contain abrasive
- Variable speed



The LS TurboShot™ blast wheel throws a high volume of shot with a bi-directional blade for an all angle blast.



The lifter makes loading and unloading easier and reduces worker fatigue.



Easy to use controls and adjustable cycle times does not require extensive training.

CATEGORY

DETAILS

| | |
|--------------------------------|----------------------------|
| Work Envelope | 30" dia. x 68" l |
| Overall Dimensions (h x l x w) | 105" x 83" x 81" |
| Impellers | 2 - 10HP |
| Dust Collector | Included |
| Production Rate | 2 - 3 minutes per cylinder |

OPTIONS:

- Manganese basket for small tanks and cylinder caps
- Service packages
- Fire suppression
- Silencer
- Factory installation (assisted)
- Electrical options
- Cap basket



Before



After

710 E. 17th St. • Wichita, Kansas 67214
 TG: 800-835-0218 • 316-265-7997
 Fax: 316-265-0013
sales@lsindustries.com
www.lsindustries.com