

LS Industries M-IDB efficiently cleans the interior surface of tanks and cylinders manually.



FEATURES:

- 6 - 15 gas cylinders every hour (varies on condition of the cylinder)
- Cylinder lift
- Speed cylinder roll will spin the cylinders during the blast cycle
- NEMA 12 electrical enclosure
- Electric and Pneumatic Controls
- All components UL and/or CSA registered
- Full load of steel shot abrasive media included
- 360-degree blast
- Easy operation
- Variable speed
- Dust Retention baffle

OPTIONS:

- DC-2 Dust Collector, 2HP, 480 CFM
- HEPA Filter for dust collector



The lifter rotates the cylinder through 300-degrees of travel for loading, blasting, and recovery of the abrasive media.



Dust retention baffle prevents dust to be carried back into the air and filter system.



Electric and Pneumatic controls.

CATEGORY

DETAILS

Blaster Dimensions (w x d x h)	46" x 96" x 72"
Blast Pot Dimensions (w x d x h)	24" x 24" x 39"
Roller Motor	0.75HP
Dust Collector Motor	1HP
Electrical Requirements	220V/3PH/60HZ (124 Amps)
Blaster Capacity (dia. x long)	10" x 62" cylinders
Dust Collector Dimension (w x d x h)	33" x 31" x 118"
Shipping Weight	1,250 lbs.

WATCH ME IN ACTION!



SCAN HERE

710 E. 17th St. • Wichita, Kansas 67214
 TG: 800-835-0218 • 316-265-7997
 Fax: 316-265-0013
 sales@lsindustries.com
 www.lsindustries.com