

LS Industries RB-2 is designed to remove paint rust, and other debris from two rims at once.



## FEATURES:

- 11% - 13% manganese steel cabinet construction
- Dual 15HP Baldor TEFC impeller motors
- Reversing LS TurboShot™ impeller wheels for thorough cleaning
- NEMA-12 electrical enclosure
- Digital shot indicating ammeters
- Full load of steel shot abrasive media
- Heavy duty four bolt flange bearings
- Automatic cycle timer
- Dual roller shafts with alignment rings to position rims for blasting



Rim Blasters have LS TurboShot™ blast wheels effectively and efficiently finish multiple types of rims.



Roller shafts are able to rotate the rims to get a consistent blast.

### CATEGORY

### DETAILS

Rim Size	Steel rims up to 23" diameter
Overall Dimensions (w x l x h)	6' x 4'6" x 8'6"
Blast Wheels (HP)	2 - 15HP
Electrical	440V/3PH/60HZ, 48 amps
Dust Collector	DC-3
Dust Collector Dimensions (w x d x h)	30" x 44" x 115"
Cabinet Construction	11 - 13% Manganese Steel
Shipping Weight (lbs.)	3,600

## OPTIONS:

- Upgrade to 20HP impeller motors
- Alternate electrical



The control panel will quickly and easily monitor and adjust performance.



Before



After

710 E. 17th St. • Wichita, Kansas 67214  
 TG: 800-835-0218 • 316-265-7997  
 Fax: 316-265-0013  
[sales@lsindustries.com](mailto:sales@lsindustries.com)  
[www.lsindustries.com](http://www.lsindustries.com)