

Our 36x30 Structural Blaster is designed to remove rust, dust, dirt, and other contaminants off I-beams.



CATEGORY	DETAILS
Work envelope (w x h)	36" x 30"
Overall dimensions (l x w x h)	36' x 9' x 15'3"
No. of blast wheels (STD)	4 - 20HP
Conveyor roller spacing	42"
Conveyor roller height	39"



FEATURES:

- Replaceable manganese blast cabinet
- Shot adder
- · Heavy duty manganese rollers
- Digital amp meters

OPTIONS:


- · Parts blow off
- Maintenance/Service platform
- Full upper air wash
- Elevator jam auto shutdown
- Magnetic shut valves
- · Parts sensor
- Shot hopper with high/low shot sensor
- Side air wash
- HMI/PLC touchscreen
- Extension conveyors
- VFD (Variable Frequency Drives)



The blaster is designed for long life as well with the heavy-duty manganese blast cabinet and easily replaceable manganese wear liners.



Parts are carried on conveyor rollers throughout. Parts blow off to help recycle shot for next time use.



LS SureShot™ wheel throws a medium volume of shot at a high velocity to achieve the desired blast finish.

710 E. 17th St. • Wichita, Kansas 67214 TG: 800-835-0218 • 316-265-7997 Fax: 316-265-0013 sales@Isindustries.com www.lsindustries.com